



Wire Rope Slings

3 Part EIPS Slings



COMPONENT WIRE ROPE DIAMETER (INCHES)	VERTICAL CAPACITY IN TONS OF 2,000 LBS.	CAPACITY IN VERTICAL BASKET	SLING BODY DIAMETER (INCHES)	EYE LENGTH (INCHES)	WEIGHTS IN LBS. per FOOT (APPROX)
3/8	3.6	7.2	3/4	10	1.04
1/2	6.4	14.4	1	14	1.84
9/16	8.0	16.0	1 1/8	16	2.36
5/8	9.9	19.8	1 1/4	18	2.88
3/4	14.0	28.0	1 1/2	20	4.20
7/8	19.0	38.0	1 3/4	24	5.70
1	24.8	49.6	2	28	7.40
1 1/8	31.2	62.4	2 1/4	32	9.40
1 1/4	38.4	76.8	2 1/2	36	11.60
1 3/8	46.0	92.0	2 3/4	40	14.00
1 1/2	55.0	110.0	3	44	16.60
1 3/4	73.0	146.0	3 1/2	52	22.70
2	95.0	190.0	4	56	29.50
2 1/4	118.0	236.0	4 1/2	64	37.40
2 1/2	145.0	290.0	5	72	46.40
2 3/4	173.0	346.0	5 1/2	80	64.00
3	204.0	408.0	6	88	66.40
3 1/2	270.0	540.0	7	96	90.80

ALL SLINGS PROOF TESTED TO 2 TIMES WORKING LOAD LIMIT. DESIGN FACTOR IS 5:1. WHEN USING IN BASKET OR CHOKER CONFIGURATION, TAKE LIFTING ANGLES INTO CONSIDERATION.

TO OBTAIN FULL RATED CAPACITY, THE PIN THAT THE EYE OF THE SLING PASSES OVER MUST BE A MINIMUM OF 4 TIMES THE DIAMETER OF THE COMPONENT WIRE ROPE.