



HHIperLift High Performance Roundslings

| HHI Part Number Endless Roundslings | HHI Part Number Eye and Eye Roundslings | Vertical WLL in M Ton | Choker Hitch WLL in M Ton | Vertical Basket WLL in M Ton | Approx. Wgt/Ft Length (lbs.) | Cross Sectional Surface Area | Recommended G-2160 Wide Body Shackle | | |
|--|--|-----------------------|---------------------------|------------------------------|------------------------------|------------------------------|--------------------------------------|--------------------|-----------------------|
| | | | | | | | G-2160 Wide Body Shackles | Bow Diam. (inches) | Inside Width (inches) |
| HH-18T-SP | HH-18T-SPE | 18t | 14.4t | 36t | 1.24 | 1.1 | 30t | 3.13" | 5" |
| HH-25T-SP | HH-25T-SPE | 25t | 20t | 50t | 1.65 | 1.47 | 30t | 3.13" | 5" |
| HH-50T-SP | HH-50T-SPE | 50t | 40t | 100t | 3.31 | 2.93 | 55t | 4.5" | 7" |
| HH-75T-SP | HH-75T-SPE | 75t | 60t | 150t | 4.96 | 4.4 | 75t | 4.75" | 7.28" |
| HH-100T-SP | HH-100T-SPE | 100t | 80t | 200t | 6.61 | 5.87 | 125t | 5.91" | 8.66" |
| HH-125T-SP | HH-125T-SPE | 125t | 100t | 250t | 8.27 | 7.34 | 125t | 5.91" | 8.66" |
| HH-150T-SP | HH-150T-SPE | 150t | 120t | 300t | 9.92 | 8.8 | 200t | 8.07" | 10.82" |
| HH-175T-SP | HH-175T-SPE | 175t | 140t | 350t | 11.57 | 10.27 | 200t | 8.07" | 10.82" |
| HH-200T-SP | HH-200T-SPE | 200t | 160t | 400t | 13.23 | 11.74 | 200t | 8.07" | 10.82" |
| HH-225T-SP | HH-225T-SPE | 225t | 180t | 450t | 14.88 | 13.2 | 300t | 10.38" | 12.62" |
| HH-250T-SP | HH-250T-SPE | 250t | 200t | 500t | 16.53 | 14.67 | 300t | 10.38" | 12.62" |
| HH-275T-SP | HH-275T-SPE | 275t | 220t | 550t | 18.19 | 16.14 | 300t | 10.38" | 12.62" |
| HH-300T-SP | HH-300T-SPE | 300t | 240t | 600t | 19.84 | 17.6 | 300t | 10.38" | 12.62" |
| HH-350T-SP | HH-350T-SPE | 350t | 280t | 700t | 23.15 | 20.54 | 400t | 12.6" | 14.56" |
| HH-400T-SP | HH-400T-SPE | 400t | 320t | 800t | 26.46 | 23.47 | 400t | 12.6" | 14.56" |
| HH-450T-SP | HH-450T-SPE | 450t | 360t | 900t | 29.76 | 26.41 | 500t | 13.39" | 17.72" |
| HH-500T-SP | HH-500T-SPE | 500t | 400t | 1,000t | 33.07 | 29.34 | 500t | 13.39" | 17.72" |

*Larger Capacities Available Upon Request

Made with Honeywell Spectra® Fibers.

4 Layer DuraFab® Cover w/Parallel laid Yarn, High Contact Rigging Efficiency, Rated Capacity & 5 to 1 Design Factor, Maximum 3.8% Elongation, Excellent Fatigue & Cut Resistance, Good UV Resistance, Traceability also available with HHIperLift Clear® Inspectable Cover.



Endless Roundslings



Eye and Eye Roundslings