



Holloway

Holloway Houston introduces our **Hammerhead Endless Slings**. They are produced using the highest strength synthetic rope, Plasma.

Plasma 12-Strand is manufactured from High Modulus PolyEthylene (HMPE) that is enhanced by Cortland's patented recrystallization process. Each sling is then covered with a braided Polyester cover utilizing our priority braiding machine. Each sling is then coated with an abrasion resistant FiberLock coating. The lower load slings are color coded based on vertical working loads. Custom colors are available. Each Sling is proof loaded with certification. Custom covering utilizing fibers such as Spectra, Technora, Kevlar, etc. is available.

Features:

- Light Weight
- Repairable
- Inspection and recertification
- Low Stretch
- Easy Handling
- High Strength



HAMMERHEAD SLINGS



Rated Capacities in Pounds

Part No.	Vertical	Choker 120° or >	Vertical Basket 90°	Min length	Rope Dia.	Approx Sling Dia.	Approx wgt per linear foot of sling
HH-9-EPC	5,770	2,450	10,300	2'	3/8"	1/2"	0.09
HH-11-EPC	6,930	2,940	12,400	2'	7/16"	9/16"	0.11
HH-12-EPC	10,300	4,380	18,500	2'	1/2"	11/16"	0.16
HH-16-EPC	16,900	7,190	30,500	2'	5/8"	7/8"	0.27
HH-18-EPC	22,600	9,590	40,600	2'	3/4"	1"	0.33
HH-22-EPC	30,500	12,900	55,000	2.5'	7/8"	1-3/16"	0.49
HH-24-EPC	36,300	15,400	65,300	2.5'	1"	1-3/8"	0.59
HH-28-EPC	48,500	20,500	87,300	3'	1-1/8"	1-1/2"	0.80
HH-30-EPC	54,400	23,100	98,000	3'	1-1/4"	1-5/8"	0.91
HH-36-EPC	72,900	30,900	131,200	3.5'	1-1/2"	2"	1.29
HH-40-EPC	96,000	40,700	172,800	3.5'	1-5/8"	2-3/16"	1.65
HH-44-EPC	103,600	43,900	186,500	4'	1-3/4"	2-3/8"	1.95
HH-48-EPC	117,100	49,700	210,800	4'	2"	2-5/8"	2.28
HH-52-EPC	141,200	59,900	254,200	4.5'	2-1/8"	2-7/8"	2.73
HH-56-EPC	158,700	67,300	285,700	4.5'	2-1/4"	3"	3.05
HH-60-EPC	174,900	74,200	314,800	5'	2-1/2"	3-3/8"	3.70
HH-64-EPC	196,600	83,400	354,000	5'	2-5/8"	3-1/2"	4.18
HH-68-EPC	217,800	92,400	392,000	6'	2-3/4"	3-5/8"	4.68
HH-72-EPC	257,400	109,200	463,300	6.5'	3"	4"	5.35
HH-76-EPC	280,500	119,000	504,000	6.5'	3-1/8"	4-1/8"	5.88
HH-80-EPC	310,000	131,600	558,000	6.5'	3-1/4"	4-3/8"	6.53
HH-84-EPC	365,000	155,100	658,000	7.5'	3-1/2"	4-5/8"	7.45
HH-88-EPC	412,000	175,000	742,000	7.5'	3-5/8"	4-7/8"	8.10
HH-96-EPC	501,000	212,800	902,000	8.5'	4"	5-3/8"	9.85

*Your minimum D/d is 2:1. However, it is suggested to use the sling at a 3:1 D/d to increase the longevity of the sling's lifespan. Sling's working load is based on a 5:1 factor of safety.



WIDE BODY SHACKLE VS HAMMERHEAD SLING D/d

HHI Part Number	Rope Diameter Inches	Vertical WLL Metric Tons	G-2160 Shackle WLL (mt)	Wide Body Width (ins.)	D/d
HH-9-EPC	0.375	2.1	7	1.6	4.27
HH-11-EPC	0.4375	3.4	7	1.6	3.66
HH-12-EPC	0.5	4.69	7	1.6	3.20
HH-16-EPC	0.625	7.7	12.5	2.13	3.41
HH-18-EPC	0.75	10.26	12.5	2.13	2.84
HH-22-EPC	0.875	13.86	18	2.5	2.86
HH-24-EPC	1	16.47	18	2.5	2.50
HH-28-EPC	1.125	22.01	30	3.13	2.78
HH-30-EPC	1.25	24.71	30	3.13	2.50
HH-36-EPC	1.5	33.09	40	3.75	2.50
HH-40-EPC	1.625	43.57	55	4.5	2.77
HH-44-EPC	1.75	47.01	55	4.5	2.57
HH-48-EPC	2	53.15	55	4.5	2.25
HH-52-EPC	2.125	64.08	75	4.75	2.24
HH-56-EPC	2.25	72.02	75	4.75	2.11
HH-60-EPC	2.5	79.36	125	5.91	2.36
HH-64-EPC	2.625	89.24	125	5.91	2.25
HH-72-EPC	3	116.79	125	5.91	1.97
HH-80-EPC	3.25	140.74	200	8.63	2.66
HH-88-EPC	3.625	187.16	200	8.63	2.38
HH-96-EPC	4	227.59	300	10.38	2.60