## **Hammerhead Slings**







- High Strength
- Light Weight
- Durable
- Repairable
- Low Stretch
- ► 100% Proof Tested

Sling's working load is based on a 5:1 factor of safety.

## Rated Capacities in Pounds

Vertical

Min

			120° or >	90°	iongai		Sin ig Biai	of sling
H	HH-9-EPC	5,770	2,450	10,300	2'	3/8"	1/2"	0.09
H	H-11-EPC	6,930	2,940	12,400	2'	7/16"	9/16"	0.11
Н	H-12-EPC	10,300	4,380	18,500	2'	1/2"	11/16"	0.16
H	H-16-EPC	16,900	7,190	30,500	2'	5/8"	7/8"	0.27
Н	H-18-EPC	22,600	9,590	40,600	2'	3/4"	1"	0.33
Н	H-22-EPC	30,500	12,900	55,000	2.5'	7/8"	1-3/16"	0.49
Н	H-24-EPC	36,300	15,400	65,300	2.5'	1"	1-3/8"	0.59
Н	H-28-EPC	48,500	20,500	87,300	3'	1-1/8"	1-1/2"	0.80
Н	H-30-EPC	54,400	23,100	98,000	3'	1-1/4"	1-5/8"	0.91
Н	H-36-EPC	72,900	30,900	131,200	3.5'	1-1/2"	2"	1.29
Н	H-40-EPC	96,000	40,700	172,800	3.5'	1-5/8"	2-3/16"	1.65
Н	H-44-EPC	103,600	43,900	186,500	4'	1-3/4"	2-3/8"	1.95
H	H-48-EPC	117,100	49,700	210,800	4'	2"	2-5/8"	2.28
H	H-52-EPC	141,200	59,900	254,200	4.5'	2-1/8"	2-7/8"	2.73
Н	H-56-EPC	158,700	67,300	285,700	4.5'	2-1/4"	3"	3.05
H	H-60-EPC	174,900	74,200	314,800	5'	2-1/2"	3-3/8"	3.70
Н	H-64-EPC	196,600	83,400	354,000	5'	2-5/8"	3-1/2"	4.18
H	H-68-EPC	217,800	92,400	392,000	6'	2-3/4"	3-5/8"	4.68
H	H-72-EPC	257,400	109,200	463,300	6.5'	3"	4"	5.35
Н	H-76-EPC	280,500	119,000	504,000	6.5'	3-1/8"	4-1/8"	5.88
H	H-80-EPC	310,000	131,600	558,000	6.5'	3-1/4"	4-3/8"	6.53
H	H-84-EPC	365,000	155,100	658,000	7.5'	3-1/2"	4-5/8"	7.45
H	H-88-EPC	412,000	175,000	742,000	7.5'	3-5/8"	4-7/8"	8.10
H	H-96-EPC	501,000	212,800	902,000	8.5'	4"	5-3/8"	9.85
	-91				The state of			8
			1					