

Phase 1 Grommet

Part #: HI-CAP1

Phase 1 Grommet (Single-Part)
(Working Load Limits Are in Tons of 2000 Lbs.)

Working Load Limit @ 5:1 Design Factor



Component Rope Dia. (inches)	Diameter of Pin, Shackle Bail, Trunnion, Etc. (inches)											Minimum length (Ft)	
	3.00	3.50	4.00	4.50	6.00	8.00	10.00	12.00	16.00	20.00	24.00		30.00
1.50	27	28	29	29	31	32	34	35	36	37	37	38	5.46
1.75	34	36	37	38	40	42	44	45	47	48	49	50	6.38
2.00	43	46	47	49	52	55	57	58	61	63	64	66	7.29
2.25	49	52	55	56	61	64	67	68	72	74	76	77	8.20
2.50	58	62	65	67	73	77	81	83	86	90	92	94	9.11
2.75	67	72	76	79	85	91	95	98	103	106	109	112	10.02
3.00	77	82	87	91	99	106	111	115	120	124	128	132	10.93
3.50		102	108	114	126	136	143	148	156	161	165	171	12.75
4.00			130	137	153	168	177	184	195	201	206	214	14.57
4.50				160	181	200	212	222	235	244	250	259	16.39
6.00					250	283	306	323	346	363	375	388	21.86

Holloway Houston Inc. uses a 3, 6 and/or 12 inch diameter pin for testing purposes.

US Patent No: 6,381,939

BASKET RATINGS ALSO AVAILABLE UPON REQUEST. CONTACT US FOR MINIMUM LENGTHS.

All slings are proof-tested to 2 times working load limit. Design factor is 5:1.

Phase 2 Grommet

Part #: HI-CAP2

Phase 2 Grommet (Two-Part) (Working Load Limits Are in Tons of 2000 Lbs.)

Working Load Limit @ 5:1 Design Factor



WIRE ROPE SLINGS

PRODUCTS

Component Rope Dia. (inches)	Diameter of Pin, Shackle Bail, Trunnion, Etc. (inches)												Minimum length (Ft)
	3.00	3.50	4.00	4.50	6.00	8.00	10.00	12.00	16.00	20.00	24.00	30.00	
1.50	54	56	58	59	63	65	68	70	72	74	75	76	3.50
1.75	69	72	74	77	81	85	88	91	95	97	99	101	4.08
2.00	87	92	95	98	105	111	114	117	123	127	129	132	4.66
2.25	99	105	110	113	122	129	134	137	144	148	152	155	5.25
2.50	117	124	130	135	146	155	162	166	173	180	184	189	6.01
2.75	135	144	152	158	171	183	191	197	206	213	219	225	6.81
3.00	154	165	174	182	199	213	223	231	241	249	256	264	7.43
3.50		204	217	228	252	273	287	297	312	322	331	343	8.67
4.00			260	274	307	336	355	369	390	403	413	429	10.2
4.50				320	362	400	425	444	470	488	501	518	11.48
6.00					500	566	612	646	693	726	750	776	15.74

Holloway Houston Inc. uses a 3, 6 and/or 12 inch diameter pin for testing purposes.

US Patent No: 6,381,939

BASKET RATINGS ALSO AVAILABLE UPON REQUEST. CONTACT US FOR MINIMUM LENGTHS.

All slings are proof-tested to 2 times working load limit. Design factor is 5:1.