






# The complete solution for your lifting job

## Green Pin Tycan® lifting assembly components

Green Pin Tycan® fibre chain offers all the performance and flexibility of steel chain but is eight times lighter than steel. A choice of four sizes of lifting chain with matching fittings allows you to manufacture a complete chain assembly with a Working Load Limit of up to 14.2 tons. The chain fittings, specially developed for use with Green Pin Tycan®, include a connecting link, a shortening hook and a sling hook. The clevis of the hooks and the bearing surface of the connecting link have been specially designed to perfectly fit Green Pin Tycan® chain links. This guarantees safe assembly of the chain and its fittings.

Below, you can find an overview of the complete lifting system and complementary products currently on offer, including the article codes for individual components.






		2.6t WLL* (1 leg sling)	4t WLL* (1 leg sling)	5t WLL* (1 leg sling)	6.8t WLL* (1 leg sling)
<b>Master links</b>	 UMS UMS25	UMS18 (5.4 ton) UMTS22 (6.5 ton)	UMS22 (8.2 ton) UMTS28 (11 ton)	UMS22 (8.2 ton) UMTS28 (11 ton)	UMS25 (11.2 ton) UMTS36 (17.5 ton)
<b>Connecting links</b>	 UMJT UMJ	GPUMJT15	GPUMJT20	UMJ13 (6.8 ton)	GPUMJT30
<b>Shorteners</b>	 UCRCT G-4151 G-4153	GPUCRCT15	GPUCRCT20	GPUCRCT25 G-4151/3 (4.75 ton)	GPUCRCT30
<b>Chain</b>	 FCHLIFT	FCHLIFT1115	FCHLIFT1120	FCHLIFT1525	FCHLIFT1330
<b>Hooks</b>	 UCSCT P-6720A	GPUCSCT15	GPUCSCT20	HKK20A050	GPUCSCT30
<b>* 2 leg sling &lt; 45 degrees</b>		3.69 ton	5.65 ton	7 ton	9.6 ton
<b>* 2 leg sling 45-60 degrees</b>		2.6 ton	4 ton	5 ton	6.8 ton
<b>* 3/4 leg sling &lt; 45 degrees</b>		5.5 ton	8.5 ton	10.5 ton	14.2 ton
<b>* 3/4 leg sling 45-60 degrees</b>		3.9 ton	6 ton	7.5 ton	10.2 ton

# The complete solution for your lashing job

## Green Pin Tycan® lashing assembly components

Green Pin Tycan® fibre chain offers all the performance and flexibility of steel chain but is eight times lighter than steel. Green Pin Tycan® Lashing Chain with a lashing capacity (LC) of 10 ton or 13.6 ton and a loadbinder with hooks, specially developed for use with Green Pin Tycan®, provide the best possible load securing during transport.

Below, you can find an overview of the complete lashing system and complementary products currently on offer, including the article codes for individual components.

		10t LC	13.6t LC
<b>Loadbinder</b>	 P-7180	LCRR25ZHENT	LCRR25ZHENT
<b>Connecting links</b>	 UMJT UMJ	UMJ13 (6.8 ton)	GPUMJT30
<b>Shorteners</b>	 UCRCT G-4151 G-4153	GPUCRCT25 G-4151/3 (4.75 ton)	GPUCRCT30
<b>Chain</b>	 FCHLASH	FCHLASH1525	FCHLASH1330
<b>Hooks</b>	 UCSCT P-6720A	HKK20A050	GPUCSCT30