





	Nominal Size		Minimum Break Load (MBL)		Eye Sizes	Standard Length		Approx. Wt. per Cable		
Part No.	Dia. inch	Dia. mm	lbs	Te (tonnes)	Each End	ft	m	lbs	kg	Target Vehicles
MTR-24-EEP-25	1"	24	110,000	49.9	18"	25	7.6	9	4	Light Vehicles
MTR-36-EEP-30	1-1/2"	36	221,000	100.3	24"	30	9.1	25	11.3	Light Vehicles
MTR-48-EEP-30	2"	48	355,000	161	36"	30	9.1	47	21.3	Med. Vehic & D6-8 Dozers
MTR-56-EEP-30	2-1/4"	56	481,000	218	36"	30	9.1	65	29.5	D6-8 Dozers
MTR-60-EEP-30	2-1/2"	60	530,000	240	36"	30	9.1	79	35.8	770-780 CAT & D9 Dozers
MTR-64-EEP-35	2-5/8"	64	596,000	270	48"	35	10.7	95	43.1	770-780 CAT & D9 Dozers
MTR-72-EEP-35	3"	72	780,000	354	48"	35	10.7	125	56.7	790 Cat & D9/10 Dozers



	Nominal Size		Minimum Break Load (MBL)		Eye Sizes	Standard Length		Approx. Wt. per Cable		
Part No.	Dia. inch	Dia. mm	lbs	Te (tonnes)	Each End	ft	m	lbs	kg	Target Vehicles
MTR-16-ENP-25	5/8"	16	84,000	38	18"	25	7.6	5	2.3	Light Vehicles
MTR-18-ENP-25	3/4"	18	113,025	51	18"	25	7.6	7	3.2	Light Vehicles
MTR-22-ENP-25	7/8"	22	152,790	69	18"	25	7.6	10	4.5	Light Vehicles
MTR-24-ENP-25	1"	24	181,500	82	18"	25	7.6	16	7.3	Light Vehicles
MTR-36-ENP-30	1-1/2"	36	364,650	165	24"	30	9.1	36	16.3	Med. Vehic & D6-8 Dozers
MTR-48-ENP-30	2"	48	585,750	266	36"	30	9.1	85	38.6	770-780 CAT & D9 Dozers
MTR-60-ENP-30	2-1/2"	60	874,800	397	36"	30	9.1	103	46.7	790 Cat & D9/10 Dozers

Options for Covering the Eyes and Body

Cordura - light weight fabric available in a sewn tube or with Velcro closure. Available on the eyes or the body of the Tow Ropes.

Rhino Guard - Heavy Duty Fabric made with a blend of Nylon and Dyneema®, available in sewn tube or Velcro Closure. Also available on the eyes or the body of the Tow Ropes.

Braided Cover - We have the ability to braid over all the Tow rope or just sections of the tow rope with our Horizontal braiding machines. We can braid with either Polyester or HMPE for the ultimate abrasion protection of your Tow Rope. We can also coat the braided cover with our FiberLock abrasion resistant coating that is available in various colors.